

DA-EVAC480 8 Zone 500W Control Unit

- Easy Programming Through Software
- Integrated system (Emergency announcement, evacuation, music broadcasting)
- Extension Line Supervision
- Built-in Monitor
- 256 Voice Messages
- Up to 120 Zone Expansion
- 32 Remote Announcement Console
- External Fireman Unit Support
- Auto Log

EN 54 16



Technical Specifications

Zone Quantity	8
Fireman Microphone	5Mv, 600 Ω
Inputs	Line 1-2 385mV, 10kΩ balanced Combo XLR Line 3-6 350mV, 10kΩ, RCA
Outputs	8 Zone, 100V, Fault, Fire and reset outputs, Terminal Type
Output Power	500W
Amplifier Type	Class D
Amplifier Monitoring	Support
Line Supervision	Support
Hand Microphone (Mike)	Support
Remote Announcement Console	Max 32
Frequency Response	80Hz~20kHz
Total Harmonic Distortion (THD)	< 1% at RMS, 1kHz
S/N Ratio	>70dB
Record Output	200 mV
Voice Record Options	MP3,WMA format. TF Card, Programmable, 256 voice message option
Event Record	HEX format, 1000 log capacity
Operating Temperature	5-40°C
Humidity	<95%
Power Consumption	650W
Operating Voltage	115-230V AC 50-60 Hz
AC Fuse	250V/6,3A, renewable fuse
Dimensions	484×132×449mm
Weight	23Kg